



FROM THE MAKERS OF
THE ASHFORD FORMULA™
AND
THE RETROPLATE SYSTEM™

PRODUCT NAME

CreteClean Plus with Scar Guard

BENEFITS

- **Revolutionary, Cutting Edge Technology**
CreteClean Plus with Scar Guard is uniquely formulated to clean and condition densified and densified-polished concrete. Proprietary polar technology pulls contaminants out and up from concrete and holds it in suspension, providing maximum cleaning efficiency.
- **Green, Environmentally Friendly**
CreteClean Plus with Scar Guard is a water-based detergent based on green chemistry and contains no VOCs. Because it is so highly concentrated, less product is required for use, and therefore less needs to be purchased, shipped, and stored, greatly reducing its environmental impact.
- **Improves Floor Performance**
The chemically advanced technology of CreteClean Plus with Scar Guard elevates it from a detergent to a performance enhancing cleaning agent. Regular and frequent use of CreteClean Plus with Scar Guard can, over time:
 - ⇒ Help strengthen and harden concrete surfaces,
 - ⇒ Decrease the visibility of minor scratches and blemishes,
 - ⇒ Decrease porosity, and
 - ⇒ Help maintain the sheen of densified concrete surfaces.

TECHNICAL DATA

Form: Clear green liquid with fresh scent, weighing 8.5 lbs. per gallon (1.02 kg per liter).

Flashpoint: Not applicable.

Freezing: If product freezes, agitate to re-emulsify.

pH: 11.0 - 12.0

Packaging: 55 Gallon (208L) Drums
5 Gallon (19L) Pails

Storage Life: Two years.

Dilution Ratio: General Cleaning - 1 oz. of CreteClean Plus per gallon of water (7.8 ml/liter).
Poultice Method - 4 oz. of CreteClean Plus per gallon of water (31.2 ml/liter).

DIRECTIONS

CreteClean Plus is simple and easy to use! First, remove any debris from the area to be cleaned. CreteClean Plus can then be applied by wet mop*, automatic scrubber or other means. Remove any excess diluted CreteClean Plus and allow the concrete surface to air-dry. For enhanced results on concrete that has been treated with the Ashford Formula or RetroPlate System, periodically burnish or buff the surface with a non-aggressive pad or polishing pad. *To avoid streaking, use only a rayon mop head, and change cleaning solution every 800 - 1,000 ft² (244 - 305 m²).

Poultice Cleaning Procedures for Severe Oil Staining

Remove all loose soil and fine grit. Mop down CreteClean Plus diluted at 4 oz./gallon of water (7.8 ml/liter). Agitate the solution to assist the product in penetrating the soil's surface. Cover the wet surface with plastic film and tape down edges. Allow area to remain wet for 10 - 15 minutes or longer if possible. Remove the plastic film and dispose of soiled solution. The procedure may need to be repeated if soil leaches back to the surface as the concrete completely dries out. Note: This procedure is designed for spot removal of significant oil or grease staining. It is not a cleaning procedure.

SPECIAL CONSIDERATIONS

Several applications of CreteClean Plus may be needed to remove oil stains from concrete surfaces that have severe oil staining. Additional treatment with an oil emulsifier, such as **CreteStrip™***, may be necessary.

Additionally, acids, salts, deicers and other harmful substances should be promptly removed to avoid damage to your floor. A proper, regular, and frequent maintenance program is highly recommended. Making CreteClean Plus a part of your maintenance program will ensure superior results.

*CreteStrip™ is manufactured exclusively by Curecrete Distribution, Inc. For details, call toll free 800.998.5664.

AVAILABILITY AND COST

CreteClean Plus is manufactured exclusively for Curecrete Distribution, Inc. and Advanced Floor Products and is distributed through a worldwide network of regional factory warehouses, area sales representatives and distributors. For pricing information, please call toll free 800.998.5664 or 888.942.3144.

EXTENDED MANUFACTURER WARRANTY

Due to the superior performance achieved by regularly using CreteClean Plus with Scar Guard, floors treated with the Ashford Formula™ or RetroPlate System™ can qualify for an extension of their original Manufacturer Warranty to a Lifetime Warranty. Qualifying conditions apply. Contact Curecrete Distribution, Inc. for more information.

Curecrete Distribution, Inc. warrants this product to be free from any manufacturing defects.

TECHNICAL ASSISTANCE

For technical support and additional cleaning tips and suggestions, please contact the Technical Service Department of Curecrete Distribution, Inc. at 1.800.998.5664.

DISTRIBUTED BY

Curecrete Distribution, Inc. 1203 W. Spring Creek Pl. Springville, UT 84663 USA	Phone: 801.489.5663 Free: 800.998.5664 Fax: 801.489.3307
Advanced Floor Products P.O. Box 80533 Provo, UT 84605	Phone: 801.812.3420 Free: 888.942.3144 Fax: 801.812.3400